



SPI070-15-SERIES-A


Applications

- Noise suppression for motors : windshield wipers / power seats / power mirrors / heating and ventilation blower / HID lighting
- Engine and transmission control units
- DC/DC converters for entertainment/navigation systems
- LED drivers
- Battery power systems


Environmental data

- Operating temperature range : -55°C ~ +155°C(component)
- Storage conditions (packaged) : -25°C ~ +40°C, ≤75% RH
- Complies with AEC-Q200 standard


Dimensions [Unit : mm]



Picture



Land Pattern [Unit : mm]



Specifications

Part No.	L0 Inductance(μH) 100kHz, 1V, 0A	DCR (mΩ)		Saturation Current DC(A) a)	Heating Rating Current DC(A) b)
		TYP.	MAX.	TYP.	TYP.
SPI070-15-R47M-A	0.47 ± 20%	7.1	8.5	16	10
SPI070-15-R56M-A	0.56 ± 20%	9.1	11	14	9
SPI070-15-R68M-A	0.68 ± 20%	10	12	12	8.5
SPI070-15-R82M-A	0.82 ± 20%	14.1	17	10	8
SPI070-15-1R0M-A	1.0 ± 20%	17.5	21	9	6
SPI070-15-2R2M-A	2.2 ± 20%	45	54	7	3.8
SPI070-15-3R3M-A	3.3 ± 20%	52.5	63	5.5	3.5
SPI070-15-4R7M-A	4.7 ± 20%	70.8	85	5	3.2
SPI070-15-6R8M-A	6.8 ± 20%	112.5	135	4	2.5
SPI070-15-100M-A	10.0 ± 20%	145.8	175	3	2

Notes

- * All test data is referenced to 25 °C ambient
- a) DC current (A) that will cause L0 to drop approximately 30 %
- b) DC current (A) that will cause an approximate ΔT of 40 °C

Packing Q'ty (PCS)









- * Reel : 2,000
- * Box : 10,000



SPI070-15-SERIES-A

Performance Graph

— Inductance (uH)
— Temperature Rise (°C)





SPI070-15-SERIES-A

■ Performance Graph

— Inductance (uH)
— Temperature Rise (°C)

